



ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	37.0	± max
T:	10.0	± max
Lead Diameter	2.5	± nom
S:	19.0	± nom
L:	40.0	± nom
Coating Lead Run Down (straight Leads)	7.0	± max
B:		±
C:	7.50	± nom



Electrical Specifications

Resistance:	5.0 Ω	± 25 %
Max Steady State Current upto 65°C:	25.00	A
Max Rec. Energy Rating:	600	J
Actual Failure Instantaneous Energy:		J
Maximum Capacitance @ 120 VAC:	41,250	µf
Maximum Capacitance @ 240 VAC:	10,419	µf
Maximum Capacitance @ 440 VAC:	2,408	µf
Maximum Capacitance @ 680 VAC:	1,200	µf
Resistance @ 100% Max Current:	0.03	Ω
Resistance @ 50% Max Current:	0.08	Ω
Body Temperature at 100% Max Current:		°c
Dissipation Constant:		mw/°c
Thermal Time Constant:		Sec.
Material Type (for Beta and Curve):	H	

MS35 5R025	
Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a