



ISO9001:2008 Certified

Mechanical Specifications (mm)

| | | |
|---|------|-------|
| D: | 3.0 | ± max |
| T: | 3.0 | ± max |
| Lead Diameter | 0.5 | ± nom |
| S: | 2.5 | ± nom |
| L: | 38.0 | ± nom |
| Coating Lead Run Down (straight Leads) | | ± |
| B: | 3.00 | ± nom |
| C: | 1.20 | ± nom |



Electrical Specifications

| | | |
|---------------------------------------|--------|--------|
| Resistance: | 10.0 Ω | ± 20 % |
| Max Steady State Current upto 65°C: | 1.00 | A |
| Max Rec. Energy Rating: | 2 | J |
| Actual Failure Instantaneous Energy: | | J |
| Maximum Capacitance @ 120 VAC: | 100 | µf |
| Resistance @ 100% Max Current: | | Ω |
| Resistance @ 50% Max Current: | | Ω |
| Body Temperature at 100% Max Current: | | °c |
| Dissipation Constant: | | mw/°c |
| Thermal Time Constant: | | Sec. |
| Material Type (for Beta and Curve): | | |

| SL03 10001 | |
|--|--------------------------|
| Date: 11/11/2008 | Drawn by: Erin Landis |
| Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com | Approved By: Mehdi Samii |
| | Revision: a |