



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	30.0	±	Max
	T:	9.0	±	Max
	Lead Diameter		±	
	S:	17.1	±	Nom
	L:	21.0	±	Nom
	Coating Lead Run Down (straight Leads)	5.5	±	Max
	B:	4.80	±	Nom
	C:	0.80	±	Nom



Electrical Specifications

	Resistance:	50.0 Ω	±	25 %
	Max Steady State Current upto 65°C:	6.00		A
	Max Rec. Energy Rating:	250		J
	Actual Failure Instantaneous Energy:	500		J
	Maximum Capacitance @ 120 VAC:	17,500		μ f
	Maximum Capacitance @ 240 VAC:	4,366		μ f
	Maximum Capacitance @ 440 VAC:	1,086		μ f
	Maximum Capacitance @ 680 VAC:	541		μ f
	Resistance @ 100% Max Current:	0.30		Ω
	Resistance @ 50% Max Current:	1.05		Ω
	Body Temperature at 100% Max Current:	212.00		°c
	Dissipation Constant:	78.2		mw/°c
	Thermal Time Constant:	73		Sec.
	Material Type (for Beta and Curve):	B		

AS32 50006	
Date: 03/15/2011	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A