



ISO9001:2008 Certified

Mechanical Specifications (mm)

	D:	37.0	± max
	T:	10.0	± 2
	Lead Diameter	9.5	± nom
	S:	19.0	± nom
	L:	40.0	± nom
	Coating Lead Run Down (straight Leads)	7.0	± max
	B:	0.00	± 0
	C:	7.50	± nom



Electrical Specifications

	Resistance:	2.0	Ω	± 25 %
	Max Steady State Current upto 65°C:	35.00	A	
	Max Rec. Energy Rating:	750	J	
	Actual Failure Instantaneous Energy:	1250	J	
	Maximum Capacitance @ 120 VAC:	51,900	μf	
	Maximum Capacitance @ 240 VAC:	13,024	μf	
	Maximum Capacitance @ 440 VAC:	3,010	μf	
	Maximum Capacitance @ 680 VAC:	1,500	μf	
	Resistance @ 100% Max Current:	0.02	Ω	
	Resistance @ 50% Max Current:	0.04	Ω	
	Body Temperature at 100% Max Current:	235.00	°c	
	Dissipation Constant:	96.0	mw/°c	
	Thermal Time Constant:	65	Sec.	
	Material Type (for Beta and Curve):	C		

MS35 2R035	
Date: 02/05/2009	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A