



ISO9001:2008 Certified

**Mechanical Specifications (mm)**

D:	22.0	± max
T:	6.8	± max
Lead Diameter	1.0	± nom
S:	7.8	± nom
L:	38.0	± nom
Coating Lead Run Down (straight Leads)	5.0	± max
B:	9.35	± nom
C:	3.88	± nom



**Electrical Specifications**

Resistance:	25.0 $\Omega$	± 20 %
Max Steady State Current upto 65°C:	5.00	A
Max Rec. Energy Rating:	63	J
Actual Failure Instantaneous Energy:	275	J
Maximum Capacitance @ 120 VAC:	4,376	$\mu$ f
Maximum Capacitance @ 240 VAC:	1,094	$\mu$ f
Resistance @ 100% Max Current:	0.40	$\Omega$
Resistance @ 50% Max Current:	0.82	$\Omega$
Body Temperature at 100% Max Current:	178.00	°c
Dissipation Constant:	45.4	mw/°c
Thermal Time Constant:	104	Sec.
Material Type (for Beta and Curve):	H	

<b>SL22 25005</b>	
Date: 11/11/2008	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a